UNDERLAYMENT

HYDRASHELL25™ | HYDRASHELL50™ | HYDRASHELL HT200™



Overdelivering On Underlayment.

Our proven Hydrashell™ synthetic and self-adhered, high-temp underlayment solutions provide superior protection for your roof and everything underneath it. We use only the best materials so we can back each product with industry-leading warranties, and give every Marco customer peace of mind that's absolutely Weather-Tite.

The Marco Weather-Tite™ System

Closure

Ventilation

Fasteners

Flashing

Sealants

Underlayment

Accessories

Our underlayment products are made with only the highest quality materials. As part of the exclusive Marco Weather-Tite System, they are designed specifically for easy installation, superior performance, and tremendous value.



HYDRASHELL25


SYNTHETIC ROOF UNDERLAYMENT



- 2.5 times lighter per square than #15 felt
- 25 times stronger than #15 felt
- 180-day UV resistance
- High-strength woven fabric, polypropylene-coated on both sides
- Specially formulated anti-slip walking surface
- Printed nail locations and 3" overlap line
- 100% asphalt-free
- Made in the USA
- 100% post-consumer recycled materials
- Miami-Dade County Code approved
- ICC-ES ESR-3361


Specs

Weight Per Square: 2.0 lbs Width/Roll Length: 48"/250'



Tear Strength: 36 lbs MD/36 lbs CD

Pliability: Pass
Water Ponding: Pass
Coefficient of Friction
Static: Printed Side 1.022
Kinetic: Printed Side 1.006





HYDRASHELL²⁵

You may also need





Metal Roof Sealant



Marco's Weather-Tite[™] LP2[™] Ridge Vent



HYDRASHELL50

HEAVY-DUTY SYNTHETIC ROOF UNDERLAYMENT

The high-strength underlayment choice, backed by a limited lifetime warranty.

- 10 times lighter per square than #30 felt
- 20 times stronger than felt
- 180-day UV resistance
- High-strength woven fabric, polypropylene-coated on both sides
- Specially formulated anti-slip walking surface
- Printed nail locations and 3" overlap line
- 100% asphalt-free
- Made in the USA
- Miami-Dade County Code approved
- ICC-ES ESR-3361

Specs

Weight Per Square: 2.8 lbs
Width/Roll Length: 48"/250'
Fire Rating: UL Class A

HYDRASHELL

TO THE PROPERTY OF THE PROPERTY OF

Nail Seal Ability: Pass Water Transmission: Pass

Tear Strength: 58 lbs MD/77 lbs CD

Pliability: Pass
Water Ponding: Pass
Coefficient of Friction
Static: Printed Side 1.202
Kinetic: Printed Side 1.053





HydraShell25 and HydraShell50 install easily with 1" diameter plastic cap roofing nails or staples along a convenient, pre-printed nail pattern.



HYDRASHELL HT200

HIGH TEMPERATURE ICE AND WATER PROTECTION

Marco's premier underlayment, this peel and stick, self-adhering solution provides superior leak protection.

- Clean, easy-to-handle, self-adhering application
- Split-back release film peels off for easy installation
- Instant watertight laps
- Adheres to a variety of substrates
- Polymer-modified asphalt gives excellent pliability
- Exceptionally durable high-tensile/tear strengths
- Glass fiber reinforcement, high dimensional stability
- 30-year limited warranty
- ICC-ES-ESR-3856

Specs

Width: 36" Length: 66' 8"

Thickness: 48 mil nom.

Gross Coverage: 2 squares

Weight: 50 lb nom.

Tensile Strength, MD: 34 lbf/in Tensile Strength, XMD: 28 lbf/in

Elongation, Mod. Bit. Portion: 10% min Adhesion to Plywood @ 40° F: 2 lbs/ft of width Adhesion to Plywood @ 75° F: 20 lbs/ft of width

Thermal Stability, Max: 0.1 inch Flexibility Temperature: -20° F Tear Resistance, MD & XMD: 20 lbs

Slip Resistance: Pass

Moisture Vapor Permeance: 0.1 U.S. Perm. or less

Nail Seal Ability: Pass Waterproof Integrity: Pass ASTM Testing: D1970




Hydrashell HT200 is not only ideal for standard roofing areas (shown), but also valleys, ridges, coping joints, chimneys, vents, skylights, and low-slope sections.



HYDRASHELL

Value Through The Roof. Value drives everything we do. That's why we've delivered industry-leading customer service for more than twenty years. And that's why we developed the Marco Weather-Tite System—a comprehensive line of products that offers easy installation, remarkable building ventilation, lower utility costs, extreme durability, and outstanding warranties. If you want to build it right, buy it smart. Get more quality, more performance and more value ... from Marco.

The Marco Weather-Tite System





800.800.8590 / MarcoIndustries.com

